Specifications of FOTON AUMARK S

Reference picture







Vehicle brand		AUMARK S
Vehicle model		BJ1088VEJEA-F
Product recoginition number		1088VEJEA-0FDA07
Vehicle Cabin		Single row-2060
Whole vehicle main dimensions	Overall dimensions (LxWxH)mm	6955×2270×2370
	Inner dimensions of the cargo body (LxWxH)mm	5140×2100×550
	Wheel base (mm)	3800
	Wheel track (front/rear) (mm)	1730/1615
	Min. ground clearance (mm)	≥190
Weight data	Curb weight (kg)	3220
	Person capacity	3
	Gross vehicle weight (kg)	8500
Engine	Model	F3.8s3141(Mechanical)
	Displacement (L)	3.76
	Rated power (kw/rpm)	105
	Rated torque (N.m/rpm)	450
	Emission	Euro III
Gearbox	Brand	ZF
	Model	6S500
Clutch	Туре	φ362×φ195 single disc,dry type,diaphragm spring
Rear axle	Type/Main reducer ratio	Whole banjo type/4.33/6T loading
Suspension	Front suspension/Leaf spring number	3-leaf spring
	Rear suspension/Leaf spring number	8+6-leaf spring
Brake system	Туре	Front Rear Drum brake
		LSPV
	Parking brake	Air cut brake
	Auxiliary brake	Exhaust brake
Wheels and tyre size		6+1/7.50R16
Electric device	Rated voltage	24V
	Cruise	Cruise control
	Multimedia	Radio+MP3
Fuel tank (L)		160
Basic equipment		Clutch booster,power steering,heater,rear mirror,side bumper,tachometer,maintenance-free battery
Optional specification	AC	0
	Power window&Central control lock&remote key	0
optional specification	MP5+Reverse camera+GPS+Multiple function steering wheel	0
optional specification	MP5+Reverse camera+GPS+Multiple function steering wheel Radar	0